



2RxxA-40

| 项目<br>Item   | 规格 Specification |               |               |               |               |               |                | 单位<br>Unit |
|--|------------------|---------------|---------------|---------------|---------------|---------------|----------------|------------|
|  | 2R230<br>A-40    | 2R300<br>A-40 | 2R350<br>A-40 | 2R470<br>A-40 | 2R600<br>A-40 | 2R800<br>A-40 | 2R1000<br>A-40 |            |
| 标称直流击穿电压<br>Nominal DC Spark-over<br>Voltage (100V/S)        | 230<br>±20%      | 300<br>±20%   | 350<br>±20%   | 470<br>±20%   | 600<br>±20%   | 800<br>±20%   | 1000<br>±20%   | V          |
| 最大冲击击穿电压<br>Maximum impulse spark-<br>over voltage (1KV/us)  | 700              | 800           | 850           | 900           | 1100          | 1300          | 1500           | V          |
| 耐冲击电流 (短波)<br>Impulse discharge current<br>(8/20us, 15times) | 40               | 40            | 40            | 40            | 40            | 40            | 40             | KA         |
| 耐交流电流<br>AC discharge current<br>(50Hz, 0.2s, 5times)        | 100              | 100           | 100           | 100           | 100           | 100           | 100            | A          |
| 最小绝缘电阻<br>Minimum insulation<br>resistance                   | 10               | 10            | 10            | 10            | 10            | 10            | 10             | GΩ         |
| 最大极间电容<br>Maximum<br>capacitance (1MHZ)                      | 10               | 10            | 10            | 10            | 10            | 10            | 10             | pF         |

大通流容量，适用于电源防雷（3+1模块）、铁路电力及电力系统防护